

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 4/8/2026 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Bloem MSP-Hightack
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Construction adhesive

Title	Life cycle stage	Use descriptors
Bloem MSP-Hightack	Professional	SU19, PC1, PROC0

Full text of use descriptors: see section 16

1.3. Details of the supplier of the safety data sheet

Manufacturer

BLOEM SEALANTS B.V.
Westvlietweg 69
2495 AA Den Haag
The Netherlands
T +31 (0) 70 329 66 01
info@bloemsealants.com, info@bloemsealants.com

1.4. Emergency telephone number

Country/Area	Organisation	Emergency number
United Kingdom	National Poisons Information Service (Birmingham Centre). City Hospital. Dudley Road B18 7QH Birmingham.	0344 892 0111 Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids Not classified

Skin sensitisation Not classified

Full text of H- and EUH-statements: see section 16

VTMO statement

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane, Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine, N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Limestone substance with national workplace exposure limit(s) (GB)	CAS-No.: 1317-65-3 EC-No.: 215-279-6	30 – 50	Not classified
Di-"isononyl" phthalate substance with national workplace exposure limit(s) (GB)	CAS-No.: 28553-12-0 EC-No.: 249-079-5 REACH-no: 01-2119430798- 28	5 – 10	Not classified
trimethoxyvinylsilane; trimethoxy(vinyl)silane	CAS-No.: 2768-02-7 EC-No.: 220-449-8 EC Index-No.: 014-049-00-0 REACH-no: 01-2119513215- 52	1 – 5	Skin Sens. 1B, H317
N-(3-(trimethoxysilyl)propyl)ethylenediamine	CAS-No.: 1760-24-3 EC-No.: 217-164-6 REACH-no: 01-2119970215- 39	0.1 – 1	Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335 STOT RE 2, H373
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	CAS-No.: 100545-48-0 EC-No.: 309-629-8 REACH-no: 01-2119979085- 27	0.1 – 1	Skin Sens. 1B, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--------------------------------------------------------------------------------------------

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

No particular/specific measures required. When in doubt or if symptoms are observed, get medical advice.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water.
Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Move undamaged containers from immediate hazard area if it can be done safely. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Shovel or sweep up and put in a closed container for disposal. Store away from other materials.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid spilling the product, as this might cause falls. Avoid contact with skin. Provide good ventilation in process area to prevent formation of vapour. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well-ventilated place. Original packaging. Keep container closed when not in use. Protect from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Limestone (1317-65-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA)	10 mg/m ³ total inhalable 4 mg/m ³ respirable
WEL STEL (OEL STEL)*	30 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

*STEL value is calculated based on the TWA limit

Di-"isononyl" phthalate (28553-12-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Diisononyl phthalate
WEL TWA (OEL TWA)	5 mg/m ³
WEL STEL (OEL STEL)	15 mg/m ³ (calculated)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

DNEL and PNEC

trimethoxyvinylsilane; trimethoxy(vinyl)silane (2768-02-7)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	3.9 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	27.6 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	26.9 mg/kg bodyweight/day
Acute - systemic effects, inhalation	93.4 mg/m ³
Long-term - systemic effects, oral	300 µg/kg dw
Long-term - systemic effects, inhalation	6.7 mg/m ³
Long-term - systemic effects, dermal	7.8 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	360 µg/l
PNEC aqua (marine water)	36 µg/l
PNEC aqua (intermittent, freshwater)	2.4 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1.3 mg/kg dwt
PNEC sediment (marine water)	130 µg/kg
PNEC (Soil)	
PNEC soil	55 µg/kg
PNEC (STP)	
PNEC sewage treatment plant	110 mg/l

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	0.308 mg/m ³
DNEL/DMEL (General population)	
Long-term - local effects, inhalation	0.055 mg/m ³
PNEC (Sediment)	
PNEC sediment (freshwater)	58 µg/kg dw
PNEC sediment (marine water)	5.8 µg/kg dw
PNEC (Soil)	
PNEC soil	0.484 mg/kg dwt

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Provide adequate ventilation.

Personal protection equipment

Personal protective equipment:

Gloves.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

No special eye protection equipment recommended under normal conditions of use

Skin protection

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Hand protection:

Recommendation: Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): e.g. nitrile rubber (≥ 0.4 mm), chloroprene rubber (≥ 0.5 mm), butyl rubber (≥ 0.7 mm) and others. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Respiratory protection

Respiratory protection:

No respiratory protection needed under normal use conditions

Environmental exposure controls

Other information:

Do not eat, drink or smoke during use. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Paste.
Odour	: None.

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 20151133.501 mm ² /s
Viscosity, dynamic	: 32000000 mPa·s @ 22 °C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.588 g/cm ³ (DIN/ISO 1183-1)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Protect against frost. Do not expose to heat.

10.5. Incompatible materials

None under normal conditions.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Di-"isononyl" phthalate (28553-12-0)	
LD50 oral rat	> 10000 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Animal sex: female

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Di-"isononyl" phthalate (28553-12-0)	
LC50 Inhalation - Rat	> 4.4 mg/l air Animal: rat, Guideline: other:
trimethoxyvinylsilane; trimethoxy(vinyl)silane (2768-02-7)	
LD50 oral rat	7.34 – 7.46 ml/kg
LD50 dermal rabbit	3.36 – 4 ml/kg
LC50 Inhalation - Rat [ppm]	2773 ppm
ATE oral	7340 mg/kg bodyweight
ATE dermal	3360 mg/kg bodyweight
ATE gases	2773 ppmv/4h
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
LD50 oral rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	5.05 mg/m ³
LD0, oral, rat	≥ mg/kg bw
LC0, Inhalation, rat	≥ 5.05 mg/l/4h
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
LD50 oral rat	1897 – 2574 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	1.49 – 2.44 mg/l/4h
ATE oral	1897 mg/kg bodyweight
ATE dermal	2000 mg/kg bodyweight
ATE vapours	1.49 mg/l/4h
ATE dust/mist	1.49 mg/l/4h
Skin corrosion/irritation	: Not classified
Limestone (1317-65-3)	
pH	8.5 – 6.5
Serious eye damage/irritation	: Not classified
Limestone (1317-65-3)	
pH	8.5 – 6.5
Respiratory or skin sensitisation	: Skin sensitization: Not classified (VTMO statement).
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Di-"isononyl" phthalate (28553-12-0)	
NOAEL (chronic, oral, animal/male, 2 years)	88.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OTS 798.3300 (Carcinogenicity)
NOAEL (chronic, oral, animal/female, 2 years)	108.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.3300 (Carcinogenicity)
Reproductive toxicity	: Not classified
Di-"isononyl" phthalate (28553-12-0)	
NOAEL (animal/female, F1)	200 – 260 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:, Guideline: EPA OTS 798.4700 (Reproduction and Fertility Effects)

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

trimethoxyvinylsilane; trimethoxy(vinyl)silane (2768-02-7)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
NOAEL (animal/female, F0/P)	250 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
NOAEL (animal/female, F0/P)	≥ 1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure : Not classified

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Di-"isononyl" phthalate (28553-12-0)	
NOAEL (dermal, rat/rabbit, 90 days)	≈ 500 mg/kg bodyweight Animal: rabbit

trimethoxyvinylsilane; trimethoxy(vinyl)silane (2768-02-7)	
LOAEL (oral, rat, 90 days)	62.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	< 62.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.1 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 1545 mg/kg bodyweight Animal: rat
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Bloem MSP-Hightack	
Viscosity, kinematic	20151133.501 mm ² /s

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Viscosity, kinematic	3.1 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards

No additional information available

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Di-"isononyl" phthalate (28553-12-0)	
LC50 - Fish	> 102 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea	> 74 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae	> 88 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

trimethoxyvinylsilane; trimethoxy(vinyl)silane (2768-02-7)	
LC50 - Fish	191 mg/l
EC50 - Crustacea	168.7 mg/l
EC50 72h - Algae	89 mg/l

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LL50, fish, short term	10 mg/l (4 Hours)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
LC50 - Fish	597 mg/l
EC50 - Crustacea	81 mg/l
EC50 72h - Algae	11 mg/l
EC50 72h - Algae [2]	352 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

12.2. Persistence and degradability

Bloem MSP-Hightack	
Persistence and degradability	Rapidly degradable

Limestone (1317-65-3)	
Persistence and degradability	Rapidly degradable

Di-"isononyl" phthalate (28553-12-0)	
Persistence and degradability	Rapidly degradable

trimethoxyvinylsilane; trimethoxy(vinyl)silane (2768-02-7)	
Persistence and degradability	Rapidly degradable

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
Persistence and degradability	Rapidly degradable

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Persistence and degradability	Rapidly degradable

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

Di-"isononyl" phthalate (28553-12-0)

BCF - Fish [1]	(183.8 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	8.8 – 9.7 @ 25 °C / pH 4.6

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Partition coefficient n-octanol/water (Log Pow)	5.86
-------------------------------------------------	------

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Partition coefficient n-octanol/water (Log Pow)	-4 – -0.3 @ 20 °C / pH 2 - 9
-------------------------------------------------	------------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Bloem MSP-Hightack

Other information	Avoid release to the environment.
-------------------	-----------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available.				

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	trimethoxyvinylsilane; trimethoxy(vinyl)silane ; N-(3-(trimethoxysilyl)propyl)ethylenediamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
52(a)	Di-"isononyl" phthalate	Phthalates: Di-"isononyl" phthalate (DINP)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

GEV - EMICODE

EC 1 PLUS

very low emission

SECTION 16: Other information

Abbreviations and acronyms:

CAS-No.	Chemical Abstracts Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
ED	Endocrine disruptor
EC-No.	European Community number
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant

Boem MSP-Hightack

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
ThOD	Theoretical oxygen demand (ThOD)
SDS	Safety Data Sheet
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative

Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH208	Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane, Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine, N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Full text of use descriptors

PC1	Adhesives, sealants
PROC0	Other
SU19	Building and construction work

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. Not classified		Expert judgement
Skin Sens. Not classified		Expert judgement

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.