

Acryl-Crackfree®

High-quality, paintable acrylic sealant

TDS: Acryl Crackfree 2403EN

Acryl-Crackfree is an acrylic based sealant that can be painted over very well with water-based and solvent-based paints. Use of Acryl-Crackfree prevents paint problems such as crackles and discoloration of the paint.



Applications

- Sealing of cracks and seams to be overpainted
- For black sides of door frames and window frames
- Along window sills, partitions, ceilings, baseboards, side boards of stairs, cover slats, decorative moldings, etc.
- Cracks in concrete, plaster and paintwork

Features and benefits

- Prevents crackle and discoloration of the paint
- Adheres to most surfaces
- Easy to process
- Easy to clean with water
- Plasto-elastic conduct after drying
- Applicable on slightly damp surfaces

Specifications

- CE-Marking, EN15651-1: F-Ext-Int: Class 7.5P
- VOC A+ Regulation

Processing

Acryl-Crackfree gives good adhesion to most building materials. Remove loose parts in advance. Substrates must be dust and grease-free, but may be slightly damp. Highly absorbent substrates such as sand-lime bricks, plaster and aerated concrete can be primed with a solution of 1 part Acryl-Crackfree on 2 parts water (as an adhesive primer). In any case of doubt, please perform adhesion tests and/or seek advice before use.

Technische eigenschappen bij 23°C en 50% luchtvochtigheid

Basis:	Dispersion acrylate
Handling temperature:	+5°C to +40°C
Temperature resistance:	-20°C to +80°C
Resistance to temperatures during transportation:	Up to -15°C
Tooling time:	10 to 30 min
Elongation at break:	200%
Hardness:	±40° Shore-A
Tensile strength, DIN53504:	0,7 N/mm ²
Flow, ISO7390:	Nil
Movement capability:	7,5%
Organic solvent:	0,0% VOC (EC)

Standard color

White, Ral9010

Packing

Cartridges of 310ml

Paint ability

Acryl-Crackfree is generally paintable with water-based and solvent-based paint systems. The best results for repainting Acryl-Crackfree are achieved after complete curing of the joint. If in doubt, we recommend that you test yourself first.

Handling

Extrude with a standard hand or cordless electric caulking gun. Finish joints with water before skin formation using a putty knife or rubber spatula. Prevent tooling traces on porous substrates such as brick or concrete. If this has happened, remove traces with plenty of water and a soft brush.

Limitations

Do not use for applications where joints are exposed to constant water immersion and joints underground. Protect fresh joints against rain for at least 5 hours during skin formation. Do not apply to PE, PP, PC, Teflon, neoprene and bitumen.

Storage and use

Store dry and cool between +5°C and +25°C, in its original sealed packing. Use best before 12 months after production.

Safety Precautions

Avoid long-lasting contact with skin. In case of contact with the eyes, rinse with plenty of water and consult a doctor. Avoid any contact with food as long as the sealant is not fully cured. Keep away from children. The product is not hazardous when applied properly and correctly. Material Safety Data Sheets (MSDS) can be obtained upon request.

Transportation classification

No special measures required



Bloem Sealants BV | Westvlietweg 69 | NL 2495AA Den Haag | Tel.: +31 (0)70 329 66 01 | info@bloemsealants.com | www.bloemsealants.com

All supplied information is according to the latest state of technology and to the best of our knowledge. Any drawings provided are for illustrative purposes only. However, they do not imply any liability. Each user must identify and perform own tests to verify if the product is safe and suitable for use under end-use conditions. All use of the product is beyond control of the supplier, therefore such use is within the exclusive responsibility of the user and the supplier cannot be held responsible for any loss incurred through incorrect or faulty use of the products. As a part of our policy of on-going product development and testing, we reserve the right to modify, alter or change product specifications without giving notice. On all our recommendations, instructions and the delivery of our products the General Conditions of Bloem Sealants BV are applicable.